# R15IE3S-SPC3-RFID

### 15" Intel® Celeron® N6211 IP65 Stainless PCAP Chassis Panel PC



#### **KEY FEATURES**

- Intel® Celeron® Elkhart Lake N6211 processor
- SUS 316/ AISI 316 stainless steel for food and chemical industries
- Sealed to IP65 for protection against water and dust
- A true flat, easy-to-clean front surface with edge-to-edge design
- Flat multi-touch panel pc with superior readability and P-Cap technology
- Various mounting solutions, Yoke mount and VESA mount
- Waterproof ports with adapter cables for external connectivity
- Support Glove / Rain mode
- Optical bonding (optional)





#### **SPECIFICATIONS**

| Display                |   |                          |   |
|------------------------|---|--------------------------|---|
| Resolution             | 1024x768  | Size                     | 15.0 inches   |
| Contrast Ratio         | 2000:1  | Panel Brightness         | 300.0 nits  |
| View Angles            | 88,88,88,88   | Active Area              | 304.1x228.1 mm  |
| Touch / Glass          | Projected Capacitive Multi Touch Screen   |                          |   |
| System Specificat      | ion   |                          |   |
| WLAN                   | Support (Optional)  | ВТ                       | Support (Optional)  |
| Processor              | Intel® Celeron® N6211 ( up to 3.0GHz)   | Memory                   | 1 x SO-DIMM, DDR4 3200 MHz, 4GB<br>8GB (Optional)<br>16GB (Optional)  |
| Storage                | 1 x M.2 2242 B-key SSD 128GB<br>M.2 2242 B-key SSD up to 512GB (Optional)<br>1 x SATA III for 2.5" SSD/HDD up to 1TB (Optional) | Ethernet controller      | 1 x Intel® Ethernet Controller  |
| Security               | TPM 2.0   | Operating System         | Windows 11 IoT Enterprise (64 bit) (Optional)<br>Windows 11 Pro 64 bit (Optional)<br>Windows 10 IoT Enterprise (64 bit) (Optional)<br>Linux Ubuntu 22.04 (Optional) |
| RFID                   | HF RFID reader 13.56 MHz  |                          |   |
| Mechanical             |   |                          |   |
| Dimension              | 378 x 301 x 56.4 mm   | Weight                   | 6.3Kg   |
| Mounting               | VESA Mount<br>Yoke Mount  | Enclosure                | Stainless Housing   |
| Cooling System         | Fanless design  |                          |   |
| Environment            |   |                          |   |
| Operating Humidity     | 10% to 90% RH, Non-Condensing   | Operating<br>Temperature | 0°C to 45°C   |
| Storage<br>Temperature | -20°C to 60°C   | IP rating                | IP65  |
| Certification          |   |                          |   |
| Certification          | CE, FCC   |                          |   |
| IO Ports               |   |                          |   |
|                        |   |                          |   |

| Power Input | 1 x M12 waterproof connector for 12V DC | USB Port  | 1x M12 waterproof connector for 2 x USB2.0                   |
|-------------|---|-----------|--|
| LAN         | 1 x waterproof Giga LAN RJ45 connector  | Indicator | 1 x LED Indicator for power<br>1 x LED Indicator for storage |
| Control     |   |           |  |
| Button      | 1 x Power Button 1 x Reset Button       |           |  |

## Accessory

Accessory 100~240V AC to DC Adapter with waterproof

connector Power Cord

External USB cable with waterproof connector External COM cable with waterproof connector External LAN cable with waterproof connector Waterproof caps

Waterproof ca VESA screws

# Power

Power Rating 12V DC (M12 type)

#### **DIMENSIONS**

UNIT:MM

